

Product Features

- 5 Megapixel HD Network IR Waterproof Bullet Camera
- 5MP (2592 x1944) H.265 full real time coding
- 3.3-12mm Varifocal Lens with 100ft Night Vision
- 3D DNR, true WDR, HLC & BLC, ROI coding
- Support local CVBS video output and one-way audio
- Support smart analysis, including object removal detection, line crossing detection, intrusion detection, etc.
- Support DC12V power supply, PoE, Built-in Web server, NVR, CMS / VMS



5MP HD Network IR Water-proof Bullet Camera QTN8058B

Technical Specifications:

Model	QTN8058B
Image Sensor	1 / 2.5 "CMOS
Image Size	2592 × 1944
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Min. Illumination	0.03 lux @F1.2,AGC ON; 0 lux with IR
Lens	3.3 ~ 12 mm @F1.4, horizontal field of view:93.9° ~ 34.8°
Lens Mount	M12 and Φ14 optional
Day & Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Digital NR	2D / 3D DNR
Angle Adjustment	Any angle
Image	
Video Compression	H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile @Leve4.1 High Tier
Resolution	5MP (2592×1944), 4MP (2560×1440), 1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240

Main stream	60Hz : 5MP(1 ~ 30fps) / 4MP(1 ~ 30fps) / 1080P(1 ~ 60fps) / 720P(1 ~ 30fps) 50Hz : 5MP(1 ~ 25fps) / 4MP(1 ~ 25ps) / 1080P(1 ~ 50fps) / 720P(1 ~ 25fps)
Bit rate	128 Kbps ~ 10 Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Audio Compression	G.711A / U
ROI	Each ROI to be configured separately
Interface	
Network	RJ45
Audio	MIC IN × 1
Video Output	CVBS video output (BNC × 1)
Functions	
Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Protocol	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T / 28181-2011
Storage	Network remote storage
Smart Alarm	Motion Alarm
PoE	Yes
IR Distance	20 ~ 20 m optional
Water-proof	IP66
Others	
Power Supply	DC 12V / PoE
Power Consumption	< 8W
Operating Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % humidity
Dimensions (mm)	Φ 87 × 219
Weight (net)	602g
Installation	Wall mounting, pendent mounting