



## QVP82BEL



### Product Features

- ▲ Max.resolution:8MP ( 3840 × 2160 )
- ▲ Smart H.265/H.265 coding
- ▲ ICR auto switch, true day / night
- ▲ 3D DNR, true WDR, HLC, BLC and ROI coding
- ▲ 30~50m IR night view distance
- ▲ 1CH audio input
- ▲ Built-in micro SD card slot, up to 128GB
- ▲ DC12V/PoE power supply
- ▲ Support three streams
- ▲ P2P function optional
- ▲ IP 67
- ▲ Support mobile surveillance by smart phones with iOS and Android OS
- ▲ Intelligent analytics: Object abandoned/missing detection, region entrance/exiting/intrusion detection(human/vehicle classification), line crossing detection(human/ vehicle classification), video tampering detection, scene change detection, face detection, face capture, crowd density detection, heat map, human/vehicle counting, human tracking



### SPECIFICATION

Camera	
Image Sensor	1 / 2.8 "CMOS
Image Size	3840×2160
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.01 lux @ F1.2,AGC ON; 0 lux with IR 0.02 lux @ F1.6,AGC ON; 0 lux with IR
Lens	2.8mm@F1.6, Horizontal FoV:109.7°; Vertical FoV:77.2°;Diagonal FoV:116.9°
Field of View	Horizontal: 109.7°; Vertical: 77.2°; Diagonal: 116.9°
Focus	Fixed
Day&Night	ICR
Lens Mount	M12
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°

## Image

Video Compression	Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	8MP ( 3840 × 2160 ), 6MP( 3072 × 2048 ),5MP( 2592 × 1944), 4MP( 2592 × 1520 ), 2K ( 2560 × 1440 ), 3MP ( 2304 × 1296 ), 1080P ( 1920 × 1080 ), 720P ( 1280 × 720 ), D1, CIF, 480 × 240
Main Stream	60Hz : 8MP/6MP(1~20fps), 5MP/4MP/2K/3MP/1080P/720P(1~30fps) 50Hz : 8MP/6MP(1~20fps), 5MP/4MP/2K/3MP/1080P/720P(1~25fps) HFR Mode: 1080P/720P(60Hz: 1~60fps; 50Hz: 1~50fps)
Sub Stream	720P/D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream	D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	64 Kbps ~ 12 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately

## Intelligent Analytics (Smart Events)

Perimeter Protection	Line crossing, region entrance/exiting/intrusion (human/motor vehicle/ non-motor vehicle classification)
Target Counting	Line crossing human/motor vehicle/non-motor vehicle counting
Exception Detection	Scene change, video blur and video color cast detection
Face Detection	Face detection and face capture
General Intelligence	Crowd density detection, heat map, object abandoned/missing detection*

## Functions

Remote Monitoring	Web browsing, CMS remote control
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
PoE	Yes , IEEE802.3af
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Smart Alarm	Motion detection, SD card error, SD card full
General function	Watermark, IP address filtering, video mask, heartbeat, password protection, non-photosensitive switch, image distortion correction
IR Distance	30 ~50 m
Ingress Protection	IP 67

# Interfaces

Network	RJ45
Audio	1CH audio input
Storage	Built-in micro SD card slot; up to 128GB
Reset	Yes
Video Output	No

# Others

Power Supply	DC12V / PoE
Power Consumption	< 9W
Dimensions ( mm )	217.7 × 80.5 × 80.5
Operating Environment	-30 °C ~ 60°C(-22°F~140°F) Humidity: less than 95 %(non-condensing)
Weight ( net )	Approx. 0.648KG
Installation	Ceiling mounting; Wall mounting

## Dimensions

