

Product Features

- 10X Optical Zoom Indoor/Outdoor 1080P Resolution 4 in 1 AHD PTZ Camera, 5.1-51mm lens
- 4 IN 1 (AHD / TVI / CVI / CVBS) video output
- Max.25/30fps@1080p resolution
- DWDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC
- OSD menu with humanized design, easy for operation
- Max 200°/s pan & 150°tilt speed; 360° endless rotation
- Up to 128 presets, 4 auto scan, 4 tour, 4 pattern, clock functions
- Built-in 6 pc New Array IR LEDs up to 60m



10X Optical Zoom 1080P 4 in 1 (AHD/TVI/CVI/CVBS) AHD PTZ Camera QH46S

Technical Specifications:

| Model | QH46S |
|------------------------|---|
| Optical zoom | NXT2441H+IMX323 CMOS 2.0MP 5.1-51mm 10x, 0.1Lux/F1.67 Color; / 0.05 Lux/F1.67 B/W H: Appr. 64°(W) ~7.3°(T) / V:Appr. 39.1°(W) ~4.4°(T) |
| Interface | BNC |
| Max Imagine Resolution | 1920*1080p |
| Frame | 25/30 fps |
| OSD | Support |
| Communication | Control over coaxial & RS485 |
| Protocols | Pelco D/P self adaptor |
| Manual speed | Pan (0.2° ~ 200°/s) ; Tilt (0.2° ~ 150°/s) |
| Preset speed | 200°/S |
| Rotation | Continuously 360°; tilt 0 ~ 90° with auto-flip |
| Speed Proportion | Human-oriented focal length/speed adaptation |
| Preset | 128 preset, title can be edited |
| Auto-flip | Tilt down 90°, with auto-flip 180° |
| Scan | 355° programmable , 4 scan |
| Pattern | 4 patterns, time and speed can be set |
| Power up Action | Auto restore to previous PTZ and lens status after power failure |
| Idle Motion | Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period |
| Time task | Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time |
| Decoder | Built-in |
| Baud rate (RS485) | 2400 / 4800 / 9600 / 19200 bps |
| Temperature | -30 °C ~ +60 °C |
| Humidity | 0 ~ 95% (Non-condensation) |
| Protection grade | 1500v lightning-proof, surge-proof |
| Power Supply | DC12V |
| Net weight | 2kg |