



QH8521B

Product Features

- ▲ 5MP HD Analog Out put(AHD/TVI/CVI)
- ▲ 1/3" High-Performance Progressive Scan COMS
- ▲ No Delay, Lossless, Long Distance transmission Up to 400 meters
- ▲ Support 3.6mm Lens
- ▲ Support 3D NR /DWDR
- ▲ Support warm light day night full color
- ▲ Support Smart LED ,automatic adjust the brightness
- ▲
- ▲ DHCP, DDNS, PPPoE network protocol and CMS supported
- ▲ Applicable to the Financial Departments, Telecommunications, Government, schools, airports, factory, Hotels , Museum, Public transportation and Other places.

SPECIFICATION

| | | |
|----------|----------------------|--|
| Camera | Image Sensor | 1/3" 5MP Progressive Scan COMS |
| | Resolution | 2560*1920 |
| | Image System | PAL/NTSC |
| | Light ON | 3 Lux @ (F2.0, AGC ON) |
| | Electronic shutter | PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s |
| | Lens | 3.6mm |
| | LEDs | 2 PCS 3500K soft warm light |
| | SNR | >52dB (AGC off) |
| | Full color distance | 15m |
| | Video Frame Rate | 20fps |
| | Video Output | TVI/AHD/CVI/CVBS |
| Menu | D&N | Support Color/ BW |
| | DNR | Support 2D 3D NR |
| | WDR | DWDR |
| | Smart LED | Support Auto/Manual Model、 1-10 level adjust |
| | White Balance | ATW / MWB/GRAY WORLD |
| | BLC | Support |
| | Image enhance | contrast、 sharpness、 saturate、 3DNR、 2DNR、 DWDR |
| Language | English, Chinese | |
| General | Power Supply | 12VDC ± 10 %; |
| | Operating Conditions | (-20° C to 50° C), Humidity 90% or less (non-condensing) |
| | Protection level | IP66 |
| | Power Consumption | Max. 3W (Max.3W with light on) |

Dimensions

